

## Pile Lithium Chlorure de Thionyle - Li-SOCL2

Modèle	IEC	Tension (V)	Capacité (mAh)	Dimensions Dia x H (mm)	Courant		Coupure (V)	Poids (g)
					Continu	Pulsé		
LIS12130		3.6	70	12.0 x 13.0	2	5	2.0	5
LIS13170		3.6	450	13.5 x 17.0	5	25	2.0	5
LIS14250	1/2AA	3.6	1300	14.5 x 25.0	10	100	2.0	10
LIS14335	2/3AA	3.6	1450	14.5 x 33.5	10	100	2.0	13
LIS14505	AA	3.6	2400	14.5 x 50.5	20	100	2.0	20
LIS17335		3.6	1500	17.0 x 33.5	20	100	2.0	20
LIS17450		3.6	1900	17.0 x 45.0	50	200	2.0	25
LIS18505	A	3.6	3200	18.8 x 50.5	50	200	2.0	30
LIS26500	C	3.6	8500	26.2 x 50.0	100	200	2.0	54
LIS34320	1/2D	3.6	5000	34.2 x 32.0	120	300	2.0	54
LIS34615	D	3.6	16000	34.0 x 61.5	200	500	2.0	100
LIS14250M	1/2AA	3.6	800	14.5 x 25.0	100	400	2.0	10
LIS14505M	AA	3.6	1800	14.5 x 50.5	300	600	2.0	20
LIS26500M	C	3.6	6500	26.2 x 50.0	1000	1500	2.0	54
LIS34615M	D	3.6	12000	34.0 x 61.5	2000	4000	2.0	100

